



9.95 EUR

incl. 19% VAT, plus [shipping](#)

- 4x RS232 !

Support: [Manual \[EN\]](#) | [Drivers](#)

DP CyberSerial 4S PCIe

PCI Express 1-lane (x1) adapter works with PCI Express slots with different lane width Installs in any available PCI Express slot

Four high-speed 16950 UART RS-232 serial ports (9-pin) support asynchronous baud rates up to 921.6Kbps

Works as standard RS-232 port or with 5V or 12V power output for devices that require power (such as handheld scanners, table scanners, POS displays, etc.). Configurable via jumpers with silk-screened settings on PCB

Enhanced bracket design to prevent bending. Connected to PCB with washered screws for a more secure connection

Spare enhanced low profile bracket is included to work in low profile chassis Onboard power connector to provide reliable power source for devices that require power

Specifications

- Chipset: Oxford OxPCIe954
- Bus connector: PCI Express x1
- Port type: Four, 9-pin, RS-232 serial ports (via 4-port fan out cable), Male

- Compliant with PCI Express Base Specification, Revision 1.1
 - Built-in 128-byte FIFO buffers dramatically increase data transmit/receive speed, especially under Windows multitasking environment
 - Asynchronous baud rates up to 921.6Kbps
 - 4-layer PCB board: separate layers for data and grounding. Greatly reduces signal noise and loss. Delivers more reliable high-speed data transfers
 - Power consumption: 2W (max)
 - Serial port power output:
 - 5V / 0.5A (per serial port) with or without 4-pin power connector connected
 - 12V / 0.5A (total output - all serial ports share) without connecting to 4-pin power connector
 - 12V / 0.5A (per serial port) with 4-pin power connector connected
 - Product dimensions:
 - With Full height bracket: 4.72" (H) x 3.62" (W) x 0.73" (D)
 - With Low profile bracket: 3.66" (H) x 2.72" (W) x 0.73" (D)
 - Product weight: 0.11 lbs
 - Environmental conditions:
 - Operating temperature: 32 to 122 degrees F
 - Storage temperature: -4 to 140 degrees F
 - Operating humidity: 20% to 80% RH
 - Storage humidity: 10% to 90% RH
 - Certifications/Standards: FCC, CE, RoHS
 - Warranty: Lifetime limited
 - Country of origin: China
-
- Compatible with Win 10 (32-/64-bit), 8.x (32-/64-bit) / 7 (32-/64-bit) / Vista (32-/64-bit) / XP (32-/64-bit) / Server 2003 & 2008 (32-/64-bit) / Server 2008 R2 / Server 2012 R2 / 2000

Package contents:

- DP CyberSerial 4S PCIe
- Spare enhanced low profile bracket
- 4-Port fan-out cable (DFP-36pin)
- Y-split power cable
- Voltage jumpers (4pcs)
- Driver CD
- Installation guide